Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Currently Amended) A lithocell comprising:
 - a lithographic apparatus, comprising:
 - an illuminator configured to condition provide a beam of radiation,
 - a support structure configured to hold a patterning device, the patterning device configured to impart the beam with a pattern in its cross-section,
 - a substrate table configured to hold a substrate, and
 - a projection system configured to project the patterned beam onto a target portion
 - of the substrate;
 - a track comprising one or more processing devices; and
- a transport system, outside of the lithographic apparatus and the track, configured to transport the substrate along an elongate transporter pathway between the track and the lithographic apparatus, wherein the track and the lithographic apparatus are side by side along their respective long sides and the transport system extends along a short side of the lithographic apparatus, or the track, or both the lithographic apparatus and the track.
- 2. (Original) A lithocell according to claim 1, wherein the transport system comprises its own mini-environment.
- 3. (Currently Amended) A lithocell according to claim 1, wherein the track and the lithographic apparatus are placed side by side and the transport system comprises a linear transporter pathway between the track and the lithographic apparatus them.
- 4. (Original) A lithocell according to claim 1, wherein the transport system comprises at least two transporter pathways, one configured to transport the substrate from the track to the lithographic apparatus and one configured to transport the substrate from the lithographic apparatus to the track.

KUIT -- 10/784,893

Client/Matter: 081468-0308381

5. (Original) A lithocell according to claim 1, wherein the transport system comprises at

least one transport robot configured to transport the substrate along the transporter pathway.

6. (Original) A lithocell according to claim 1, wherein the transport system serves a

plurality of lithographic apparatuses.

7. (Previously Presented) A lithocell according to claim 1, comprising a plurality of

tracks.

8. (Previously Presented) A lithocell according to claim 1, wherein the transport system

serves a substrate process apparatus, a substrate metrology apparatus, or both, to form an

extended substrate assembly line.

9. (Original) A lithocell according to claim 1, wherein the transport system is formable to a

desired shape.

10. (Original) A lithocell according to claim 1, wherein the transport system comprises one

or more transporter pathways configured to transport a substrate between different processing

devices of the track.

11. (Previously Presented) A lithocell according to claim 1, wherein the transport system

comprises a conveyor in the form of a shuttle on a linear guide actuated by an electric motor,

or a pneumatic motor.

12. (Previously Presented) A lithocell according to claim 11, wherein the linear guide is a

roller bearing guide or a gas bearing guide.

13. (Previously Presented) A lithocell according to claim 1, wherein the transport system

comprises a conveyor belt configured to support the substrate transported thereon.

14. (Cancelled)

15. (Currently Amended) A lithocell comprising:

- 3 -

a lithographic apparatus, comprising:

- an illuminator configured to provide a beam of radiation,
- a support structure configured to hold a patterning device, the patterning device configured to impart the beam with a pattern in its cross-section,
- a substrate table configured to hold a substrate, and
- a projection system configured to project the patterned beam onto a target portion of the substrate;
- a track comprising one or more processing devices; and
- a transport system, external to the track and lithographic apparatus, configured to transport the substrate between the track and the lithographic apparatus, the transport system comprising a robot arm pivotable about an axis at its first end and adapted to hold a substrate at its opposite end, wherein the track and the lithographic apparatus are side by side along their respective long sides and the transport system extends along a short side of the lithographic apparatus, or the track, or both the lithographic apparatus and the track.
- 16. (Original) A lithocell according to claim 15, wherein the transport system comprises its own mini-environment.
- 17. (Original) A lithocell according to claim 15, wherein the transport system serves a plurality of lithographic apparatuses.
- 18. (Previously Presented) A lithocell according to claim 15, comprising a plurality of tracks.
- 19. (Original) A lithocell according to claim 15, wherein at least two lithographic apparatus and at least two tracks are disposed around the robot arm.
- 20. (Previously Presented) A lithocell according to claim 15, wherein the transport system serves a substrate process apparatus, a substrate metrology apparatus, or both, to form an extended substrate assembly line.
- 21. (Currently Amended) A device manufacturing method using a lithocell comprising a lithographic apparatus and a track comprising:

KUIT -- 10/784,893

Client/Matter: 081468-0308381

applying a radiation-sensitive material to a substrate in the track;

transporting the substrate to the lithographic apparatus from the track using a transporter between and external to them, wherein the track and the lithographic apparatus are side by side along their respective long sides and the transporter extends along a short side of the lithographic apparatus, or the track, or both the lithographic apparatus and the track; and

projecting a patterned beam of radiation onto a target portion of the substrate.

22. (Original) A device manufacturing method according to claim 21, wherein the transporter is configured to transport the substrate along an elongate transporter pathway between the track and the lithographic apparatus.

23. (Original) A device manufacturing method according to claim 21, wherein the transporter, external to the track and lithographic apparatus, is configured to transport the substrate between the track and the lithographic apparatus by a robot arm pivotable about an axis at its first end and adapted to hold a substrate at its opposite end.

24. (Previously Presented) A lithocell according to claim 1, further comprising an automated material handling system configured to transport substrates to or from the lithographic apparatus or track independently from the transport system.